

Delivering the Ultimate On-board Heating Solution.

Webasto Marine Coolant Heaters are an excellent addition to any vessel. Our Coolant Heaters provide on-board hot water for the galley and head, and can also deliver warm air to the cabins and compartments to keep your crew comfortable.

All Webasto Marine Coolant Heaters are available as an individual heating unit, or as part of the Webasto C⁵ Complete Cabin Climate Comfort Control system package.

WEBASTO MARINE COOLANT HEATERS

THERMO 90 ST



Coolant Heater Only

Voltage	12 Volt	24 Volt
Part No.	9015882A	9015883A
	5001012A (C ⁵ Kit 12V)	

	Mode	Thermo 90 ST
Heat output	Boost	31,000 BTU (9.1 kW)
	Operating range	6,100 - 26,000 BTU (1.8 - 7.6 kW)
Fuel		Diesel 1,2/Arctic/Kerosene
Fuel consumption	Boost	.28 gal/h (1.1 l/h)
	Operating range	.05 - .24 gal/h (0.19 - 0.9 l/h)
Rated voltage		12 V / 24 V
Rated power consumption	Boost	90 W
	Operating range	37 - 83 W
Flow rate of circulating pump U 4846 against 0.3 psi		435 gal/h (1650 l/h)
Dimensions of heater (L x W x H) * electronic control unit mounted on the heater		12 3/8 x 5 1/4 x 9 1/8 in. (314 [355*] x 133 x 232 mm)
Dimensions of electronic control unit with stand (L x W x H)		4 5/8 x 6 x 1 3/4 in. (117 x 150 x 44 mm)
Weight of heater		10.51 lbs. (4.8 kg)

DBW 2010



Coolant Heater Only

Voltage	12 Volt	24 Volt
Part No.	89235B	922502
	5001013A (C ⁵ Kit 12V)	

	DBW 2010
Heat output	45,000 BTU (11.6 kW)
Fuel	Diesel 1,2/Arctic/Kerosene
Fuel consumption	.4 gal/h (1.5 l/h)
Rated voltage	12 V / 24 V
Rated power consumption (without circulating pump)	60 W
Flow rate of circulating pump U 4846 against 0.15 psi	420 gal/h (1590 l/h)
Dimensions of heater (L x W x H)	23 x 8 x 9 in. (584 x 205 x 228 mm)
Dimensions of electronic control unit with stand (L x W x H)	4 3/8 x 4 5/8 x 2 in. (111 x 117 x 49 mm)
Weight of heater	33 lbs. (15 kg)

THERMO 230/300




Coolant Heater Only

Type	230	300
Part No.	63647B	63650B

	Thermo 230	Thermo 300
Heat output	80,000 BTU (23 kW)	104,000 BTU (30 kW)
Fuel	Diesel 1,2/Arctic/Kerosene	
Fuel consumption	.65 gal/h (2.5 kg/h)	.85 gal/h (3.3 kg/h)
Rated voltage	24 V	
Rated power consumption (without circulating pump)	65 W	110 W
Flow rate of • circulating pump U 4814 against 0.15 psi • circulating pump U 4851 against 0.4 psi	1,400 gal/h (5300 l/h) 1,600 gal/h (6057 l/h)	
Dimensions of heater (L x W x H)	24 x 9 11/16 x 8 11/16 in. (610 x 246 x 220 mm)	
Weight of heater	42 lbs. (19 kg)	

Webasto Partner:



Webasto Product North America, Inc.

15083 North Rd.
Fenton, MI 48430
Phone: (800) 215-7010
www.webasto-marine.com

